Page 3

REMARKS

Claims 1-9 have been amended, and claims 10-32 have been canceled.

Examination of the claims, as amended, is respectfully requested.

Respectfully submitted,

Darin J. Gibby Reg. No. 38,464

TOWNSEND and TOWNSEND and CREW LLP Two Embarcadero Center, 8th Floor San Francisco, California 94111-3834 Tel: (415) 576-0200 Fax: (415) 576-0300 DJG:cll

DE 7051879 v1

2

section comprises a metal tube.

VERSION WITH MARKINGS TO SHOW CHANGES MADE

1	1. (Once Amended) A catheter assembly comprising:
2	a hollow sheath having a proximal portion and a tip;
3	an elongate operative element slidably and rotatably housed within the sheath, the
4	operative element comprising a distal end and a proximal end;
5	the elongate operative element comprising a relatively stiff[, self-supporting]
6	initial section extending from [at] the proximal end thereof; [and]
7	a rotatable combined connector secured to the proximal end of the operative
8	element, said combined connector comprising a data/information connector and a mechanical
9	connector; and said combined connector comprising an angled rotary alignment surface that is
10	adapted to blind mate with a corresponding connector of a drive unit that has an angled rotary
41	alignment surface.
1 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2. (As filed) The catheter assembly according to claim 1 wherein said
i, i, i	data/information connector comprises an electrical connector.
<u>1</u>	3. (As filed) The catheter assembly according to claim 1 wherein said
₽ 2	mechanical connector comprises a rotary drive connector.
	4. (Once Amended) The catheter assembly according to claim 3 wherein
	said rotary drive connector comprises a drive surface which simultaneously extends [an] axially
⊧ ≠3	[-] and circumferentially[-extending drive surface].
1	5. (As filed) The catheter assembly according to claim 1 wherein said
2	combined connector comprises a rotary alignment surface.
1	6. (As filed) The catheter assembly according to claim 1 wherein said
2	elongate operative element comprises an imaging cable having an image element at said distal
3	end thereof.
1	7. (As filed) The catheter assembly according to claim 1 wherein said initial

1

2 3

4

- Page 5
- 1 8. (As filed) The catheter assembly according to claim 1 further comprising 2 a fluid seal between said proximal portion of said sheath and the initial section of the elongate 3 operative element.
 - 9. (Once Amended) The catheter system according to claim 1 wherein said elongate operative element comprises a flexible imaging core and a relatively stiff tube at the proximal end thereof to create a relatively stiff, self-supporting initial section of the elongate operative element extending [at the] from the proximal end thereof.

Please cancel claims 10-21.